

DESCRIÇÃO**UNID****GMC-1265****CURSOS**

X-axis	mm	1200
Y-axis	mm	650
Z-axis	mm	650
Spindle nose to table surface	mm	100-710
Spindle center to column surface	mm	740
X.Y.Z axis Ball screws dia	mm	40xpitch12

MESA

Table size	mm	1260 * 600
Working Area	mm	1200 * 650
Tee Slots (CD x W x No.)	mm	CD 100x18x5
Max. Table Load	Kg	1200

ÁRVORE

Spindle taper		BT40 / ISO40 / CAT40 opt. BT No.50 / CAT50
Belt drive	rpm	BT40:10,000(standard) opt. BT50:8,000
Direct Drive	rpm	BT40/HSK63A: 10000/12000/15000/18000 rpm BT50/HSK100A: 8000/10000/12000 rpm
Built-in Drive	rpm	BT40/HSK63A: 18000/24000/30000 rpm BT50/HSK100A: 8000/10000/12000 rpm

AVANÇOS

Cutting feedrate	mm/min	1-10,000 Depending on the controller
3-axes slideways		Hardened ground
Rapid transverse rates(X,Y,Z)	m/min	24000/24000/15000

A.T.C

Capacity-standard access	pcs	16(armless) opt. 24(armless)
Capacity-optional access	pcs	24/30(Disc type) 32/40(Chain type)
Tool selection		Bi-directional & min. path

Max. tool diameter x length	mm	Armless type:89*250 Arm type:80*250
Max. tool weight	Kg	6
Air power required		6 kg/cm ²
Tool shank		BT40/ISO40/CAT40 opt. ISO50/CAT50

Motor

Spindle drive motor	kw(HP)	std:7.5kw(10HP) opt. ZF gear box 11kw(15HP)
Coolant pump	HP	1/2
Power supply		STD:20KVA
Net wight	Kg	7700

The best solution, the best partner