| DESCRIÇÃO | UNID | GMC-1465 |
|---|---|---|
| CURSOS | | |
| X-axis | mm | 1400 |
| Y-axis | mm | 650 |
| Z-axis | mm | 650 |
| Spindle nose to table surface | mm | 100-710 |
| Spindle center to column surface | mm | 760 |
| X.Y.Z axis Ball screws dia | mm | 40xpitch12 |
| MESA | | |
| Table size | mm | 1500 * 600 |
| Working Area | mm | 1400 * 650 |
| Tee Slots (CD x W x No.) | mm | CD 100x18x5 |
| Max. Table Load | Kg | 1500 |
| ÁRVORE | | |
| Spindle tapper | | BT40 / ISO40 / CAT40<br>**opt.** BT No.50 / CAT50 |
| Belt drive | rpm | BT40:10,000(standard)<br>**opt.** BT50:8,000 |
| Driect Drive | rpm | BT40/HSK63A: 10000/12000/15000/18000 rpm<br>BT50/HSK100A: 8000/10000/12000 rpm |
| Built-in Drive | rpm | BT40/HSK63A: 18000/24000/30000 rpm<br>BT50/HSK100A: 8000/10000/12000 rpm |
| AVANÇOS | | |
| Cutting feedrate | mm/min | 1-10,000<br>Depending on the controller |
| 3-axes slideways | | Hardened ground |
| Rapid transverse rates(X,Y,Z) | m/min | 24000/24000/15000 |
| A.T.C | | |
| Capacity-standard access | pcs | 16(armless)<br>**opt.** 24(armless) |
| Capacity-optional access | pcs | 24/30(Disc type)<br>32/40(Chain type) |
| Tool selection | | Bi-directional & min. path |
| Max. tool diameter x length | mm | Armless type:89*250<br>Arm type:80*250 |
| Max. tool weight | Kg | 6 |
| Air power required | | 6 kg/cm² |
| Tool shank | | BT40/ISO40/CAT40<br>**opt.** ISO50/CAT50 |

| Motor | | |
|---|---|---|
| Spindle drive motor | kw(HP) | std:7.5kw(10HP)<br>**opt.** .ZF gear box 11kw(15HP) |
| Coolant pump | HP | 1/2 |
| Power supply | | STD:20KVA |
| Net wight | Kg | 8200 |

*The best solution, the best partner*